

# BUILDING PERFORMANCE

## Class 1 Building Product Information Sheet



**PRODUCT NAME:** CM Promo Underlay

**PRODUCT LINE:** CM Promo Underlay

### PRODUCT DESCRIPTION AND ITS INTENDED USE:

CM Promo Underlay is manufactured using recycled polyurethane foam, which is granulated and bonded together with a polyurethane binder, peeled to thickness, laminating film and quadmesh applied to the top of the cushion and then packaged. It is conventionally laid under carpet.

### KEY TECHNICAL SPECIFICATION:

|                                                        |
|--------------------------------------------------------|
| Thickness: 12mm +/- 7.5%                               |
| Width: 1800mm +/- 1%                                   |
| Roll Length: 10 mtrs +/- 1%                            |
| Density: 110 kg / m <sup>3</sup> +/- 7.5%              |
| Laminate: Top - Plain silver film & clear 7mm webbing. |
| AS4288:2003 - Luxury Use                               |

**PRODUCT IDENTIFIER:** UL2012 - CM Promo 12mm

**PLACE OF MANUFACTURE:** Aotearoa, New Zealand

### LEGAL AND TRADING NAME OF THE MANUFACTURER:

Dunlop Flooring Limited - 3446651

**ADDRESS:** 680 Rosebank Road, Avondale, Auckland 1026

**WEBSITE:** [www.dunlopflooring.co.nz](http://www.dunlopflooring.co.nz)

**EMAIL ADDRESS:** [sales@dunlopflooring.co.nz](mailto:sales@dunlopflooring.co.nz)

**PHONE NUMBER:** +64-9-905-2680

**NZBN:** 9429031040419

# BUILDING PERFORMANCE

## Class 1 Building Product Information Sheet

### Relevant Building Code Clauses:

**B2 Durability:** Performance clauses B2.3.2(a)

**C3 Fire affecting areas beyond the fire source:** Performance clause C3.4(b)

**G6 Airborne and Impact Sound:** Performance clauses G6.3.1 and G6.3.2

### Statement on how the Building Product is expected to contribute to Compliance:

**B2.3.2(a): Durability** – CM Promo Underlay is a flooring component placed underneath the conventionally laid carpet. New CM Promo Underlay is guaranteed to perform for the life of the new carpet.

**C3.4(b): Fire Performance** – There are no specific requirements for detached dwellings, within household units in multi-unit dwellings, or outbuildings and ancillary buildings.

For all other areas, minimum critical radiant flux fire testing results are required for both the carpet and the carpet underlay to be used and tested to ISO 9239-1:2010. Dunlop Flooring or the Carpet Manufacturer/Distributor should be contacted to confirm if test results are available for the relevant combination and if they meet the requirements for the proposed installation area.

**G6.3.1 and G6.3.2: Airborne and Impact Sound** – This is only a requirement for building elements which are common between occupancies to limit noise transfer from other occupancies or common spaces. In these situations, the floor itself should be constructed to ensure that the Sound Transmission Class and Impact Insulation Class requirements are less than 55. The underlay and carpet will contribute positively to the result. However, determining that result, requires technical support from an architect familiar with prior results of the same construction or actual in-house testing.

### Limitations on the use of the Building Product:

CM Promo Underlay is intended to be laid directly onto a bare floor, and then have the carpet conventionally laid directly on top of the underlay.

Per industry standard AS/NZS 2455.1:2007, new carpet should always be installed on new underlay.

**It should only be installed where the floor surface is:**

- **Clean** – from dust and grit, and any surface contaminants have been safely removed.
- **Sound** – floor will not crumble, move, crack or break up.
- **Flat** – floor is flat or level.
- **Smooth** – no lumps or bumps or sharp lipping.
- **Dry** – no visible signs of any moisture. New concrete floors should be tested to ensure the level is 75% RH or less when measured with a hygrometer.

**CM Promo Underlay is:**

- Not suitable to be installed in any space containing sanitary fixtures / appliances where the floor is likely to be splashed or contaminated during its intended use.
- Not waterproof – in the event of contamination by a major spill / flooding, then it is recommended to be replaced as the warranty no longer applies in that event.
- not suitable to be laid on top or underneath other underlays.
- not suitable to be used without carpet.
- able to be used for under-floor heating with direct heat at less than 40 degrees Celsius. However, it is recommended that the carpet and flooring tog rating is less than 2.5 to get the best results out of under-floor heating. Higher tog ratings will reduce the effectiveness of the under-floor heating system.

Consideration needs to be made where the carpet supplier has special installation instructions due to the type of carpet.

# BUILDING PERFORMANCE

## Class 1 Building Product Information Sheet

### Design Requirements that would support the use of the Building Product:

Insulation: CM Promo Underlay contributes positively to the thermal insulation of the floor.

### Installation Requirements:

It is recommended that the flooring is installed by a professional. They should be trained and experienced at installing carpet and follow the Floor NZ Best practice guidelines and/or AS/NZS2455.1:2007 installation requirements. The carpet supplier may have special installation requirements for speciality carpets that should be followed.

#### Floor NZ Best practice guidelines:

[Technical Flooring Guidelines | FloorNZ](#)

Textile flooring coverings - installation standard: AS/NZS 2455.1:2007

[AS/NZS 2455.1:2007: Standards New Zealand](#)

Soft Underlay Standard: AS 4288 - 2003

[AS 4288-2003 Soft underlays for textile floor coverings \(saiglobal.com\)](#)

### Maintenance Requirements:

It is recommended that the carpet maintenance guidelines are followed as per the carpet supplier.

If the CM Promo Underlay becomes damp or wet from minor spills, it is recommended that a flooring professional cleans and dries the product, or if unable to replace the section, to ensure there are no subsequent issues arising due to the contamination.

Is the Building Product subject to warning or ban under section 26:

No